



FLOPLUS PROTECT

PFOA/PFOS FILTRATION







FLOPLUS PROTECT

PFOA/PFOS FILTRATION







Specifications

Parts to assemble the system:

Housing Big blue $150253\,1\,½$ » I/O BSP with pressure relief; 655223-43 FloPlus Protect cartridge

Accessories for installation:

144368 wrench SW-4 for Big blue 20» 150061 bracket with screws

Technical specifications

- Housing size 20"
- ▶ Inlet size 1 ½" BSP
- ▶ Housing material Polypropylene
- **Housing dimensions** 590 mm x 189 mm (23.22" H x 7.45" W)
- Cartridge type Fibredynecarbon block 655223-43 FloPlus Protect cartridge
- Cartridge dimensions 118 mm x 508 mm (4 5/8" x 20")
- Micron rating 0.5
- ▶ Approximate filter life* 4 5 months
- **Capacity** 56 781 liters (15 000 gallons)
- Flow rate 18.9 Lpm (5 gpm)
- Feed pressure range 2.06 6.20 bar (30 90 psi)
- **Temperature range** 4.4 37.8°C (40° 100°F)
- Replacement cartridge (Model/Part No.) FloPlus Protect 20BB / 655223-43 (6/Case)

INSTALLATION TIPS

- Choose a mounting location suitable to support the full weight of the system when operating.
- Make sure to properly lubricate 0-ring prior to use.
- Install vertically with bowl hanging down.
- ▶ Allow 2-1⁄2" (6.35 cm) clearance below the cartridge for easy cartridge replacement.

OPERATION TIPS

- ▶ Replace cartridge if flow rate decreases.
- Do not exceed service flow rate.
- Inspect 0-ring during each cartridge change. Lubricate and/or replace if necessary.

SIZING

▶ Service flow rate: maximum 18.9 L/min.

www.pentair.eu

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners.

^{*} Filter life dependent on gallon usage and overall incoming water quality.

^{*}The model FloPlus Protect 20BB, assembly of Big Blue housing 20» 1½» I/O and Flow plus protect housing is tested by IAPMO R&T against NSF/ANSI 53 for the reduction of perfluorooctanoic acid (PFOA) and perfluorooctane sulfonate (PFOS).