

CHLORPLUS PROTECT™ 10

PFOA/PFOS FILTRATION



CHLORPLUS PROTECT™ 10

PFOA/PFOS FILTRATION



SPECIFICATIONS

Parts to assemble the system:

150102 housing Black/blue ¾" I/O with pressure relief
655226-43 ChlorPlus Protect 10 Cartridge

Accessories for installation:

150295 Wrench SW-2 150578 Bracket with screws

SPECIFICATIONS

- ▶ **Housing size** 10"
- ▶ **Inlet size** ¾" BSP
- ▶ **Housing material** Polypropylene
- ▶ **Housing dimensions** 130 mm x 310 mm (5.13"W x 12.45" H)
- ▶ **Cartridge type** Carbon block 655226-43 ChlorPlus Protect cartridge
- ▶ **Micron rating** 1
- ▶ **Approximate filter life*** 4 - 5 months
- ▶ **Capacity** 3785 liters (1000 gallons)
- ▶ **Flow rate** 3.78 L/min (1 gpm)
- ▶ **Feed pressure range** 2.06 - 8.6 bar (30 - 120 psi)
- ▶ **Temperature range** 4.4 - 37.8°C (-40° - 100°F)
- ▶ **Replacement cartridge** (Model/Part No.) ChlorPlus Protect 10 / 655226-43 (12/Case)

*Filter life dependent on gallon usage and overall incoming water quality.

The model ChlorPlus Protect 10, assembly of Pentair std housing 10» ¾" I/O and Chlorplus protect 10 cartridge is tested by IAPMO R&T against NSF/ANSI 53 for the reduction of perfluorooctanoic acid (PFOA) and perfluorooctane sulfonate (PFOS).

INSTALLATION TIPS

- ▶ Choose a mounting location suitable to support the full weight of the system when operating.
- ▶ Make sure to properly lubricate O-ring prior to use.
- ▶ Install vertically with bowl hanging down.
- ▶ Allow 1-½" (3.81 cm) clearance below the cartridge for easy cartridge replacement.

OPERATION TIPS

- ▶ Replace cartridge if flow rate decreases.
- ▶ Do not exceed service flow rate.
- ▶ Inspect O-ring during each cartridge change. Lubricate and/or replace if necessary.

SIZING

- ▶ Service Flow Rate: 3.78 L/min (1 gpm).

www.pentair.eu

All indicated Pentair trademarks and logos are property of Pentair. Third party registered and unregistered trademarks and logos are the property of their respective owners.

MKT-TS-196-EN-A © 2024 Pentair. All rights reserved.