



# TECHNICAL SHEET

## ACCESSORIES

CABINETS SOFTFLO





## CABINETS SOFTFLO

### TECHNICAL CHARACTERISTICS

- Appliance style design
- Designed for 5600 and 5000 valves with SE electronics
- Also available with standard mechanical 5600 Time Clock or Metered with blind face plate
- Customised labels on request
- Available in three sizes, for 18», 30» & 35» vessels
- Direct access to electronic functions with integrated front panel
- Brine compartment and valve easily accessible under removable cover
- Brine well and drain elbow included
- Large salt opening with easily detached snap-fit lid
- Foam baffle protects electronic controls from brine vapors
- Blow-molded cabinet with injection-molded cover and salt lid
- Molded features at top and bottom of cabinet hold mineral tank in place
- Integral side handles allow easy installation and positioning
- Available in contemporary Cool Gray



Materials	
Cabinet material	Polyethylene
Cover material	Polystyrene
Salt lid material	Polystyrene
Control panel material	ABS
Nominal dimensions in mm	
Overall height with cover	648 - 990 - 1130
Width	324
Depth	584
For vessels size	Salt Capacity (1 <sup>st</sup> fill)* in kg
8" x 18" 10" x 16"	25
7" x 30" 8" x 30"	50
7" x 35" 8" x 35" 9" x 35" 10" x 35"	75

\* Capacity of salt is indicated for first fill, and is subjected to variation.

