

TECHNICAL SHEET

FLECK
ELECTRONIC CONTROLLER
XTR/HURRICANE



** PENTAIR TECHNICAL SHEET



FLECK ELECTRONIC CONTROLLER - XTR/HURRICANE



TECHNICAL CHARACTERISTICS

- Time of day super capacitor backup
- Large color LCD touch screen display
- Programmable relay output
- Remote lockout and regen input
- Easy electronic programming
- Error alarm
- Assistance screen with dealer contact information
- Programmable assistance interval with alarm for service
- Master settings by category
- Intuitive navigation
- Field programmer for quick configuration and diagnostic data download to PC via USB
- Password lockout screen
- Vacation mode to save water when not in use
- Diagnostics:
- Current flow rate
- Peak flow rate (can be reset)
- Totalizer (can be reset)
- Last regeneration
- Daily usage for last four weeks
- Reserve

- Software version
- Number of regenerations
- Regeneration interval
- Usage since last regeneration
- Last program change

| - | | | | | 11.7 |
|-----|------|-------|------|---------|------|
| CUI | NTRO | LLERS | PEUI | -ICAIIC | 71 |

| System type | System Type 4 |
|-------------|------------------|
| Valve type | 5800, 5810, 5812 |

www.pentairaquaeurope.com