



TECHNICAL SHEET

PENTAIR

RO-2500 REVERSE OSMOSIS
DRINKING WATER SYSTEM





PENTAIR RO-2500* REVERSE OSMOSIS DRINKING WATER SYSTEM

TECHNICAL CHARACTERISTICS



- The finest level of water filtration available – filtering particles as small as 1/1000 of a micron
- Reduces bad taste & odor, chlorine taste & odor, sediment, arsenic III, arsenic V**
- Designed for use on chlorinated or non-chlorinated water supplies
- Comes complete with cartridges, a long-reach faucet, and installation hardware
- Great-tasting water for drinking and cooking
- Significantly less expensive than bottled water, with a reduced impact on the environment
- Produces clear, hard ice

APPLICATIONS

- Residential point-of-use drinking water
- Undersink installation
- Pretreatment for icemakers

SPECIFICATIONS

Maximum dimensions:

| | |
|----------------------|--|
| System | 394 x 356 x 133 mm 15½ (W) x 14 (H) D x 5¼ (D) inches |
| Tank | 343 x 229 x 203 mm 13½ (W) x 9 (H) D x 8 (D) inches |
| Pressure range | 2.07-8.6 bar (30-125 psi) |
| Filter life | 6-12 months*** |
| Membrane performance | 132.5 L per day (35 gpd) |

* Not performance tested or certified by NSF
 ** Based on manufacturer's internal testing
 *** Dependent on daily water consumption